Flexlite TX - X5 FastMig

reddot winner 2020
industrial design



ПРЕИМУЩЕСТВА

- Flexible cable set with leather sheathing protection maximizes durability
- Innovative torch design increases user comfort by reducing wrist loading
- Silicone rubber material gives a firm grip on the handle
- Kemppi consumables guarantee high quality and cost-effectiveness for your welding
- Torch models available with or without a trigger switch
- Optional switch extension increases trigger control accuracy

КРАТКОЕ ОПИСАНИЕ

Flexlite TX models compatible with X5 FastMig

Level 3
TX 223GE
TX 253WSE
TX 353WE

In model names: G = Gas-cooled, W = Water-cooled, E = Euro connector

ТЕХНИЧЕСКИЕ СПЕЦИФИКАЦИИ

	TX 223G	TX 253WS	TX 353W
Стандарты	IEC 60974-7	IEC 60974-7	IEC 60974-7
Тип охлаждения	Газ	Вода	Вода
Тип соединения (ток-газ)	R1/4	R1/4 и R3/8	R1/4 и R3/8
Допустимая нагрузка при 40 % (аргон)	220 A	250 A	350 A
Допустимая нагрузка при 100 % (аргон)	-	200 A	250 A
Тип соединения (управление)	4-контактный	4-контактный	4-контактный
Тип соединения (охлаждение)	-	R1/4&R3/8	R1/4&R3/8
Пульт дистанционного управления	Нет	Нет	Нет
Тип шейки	Угол 70°	Поворотная	Угол 70°

Flexlite TX - X5 FastMig /
Технические спецификации